Easee Equalizer Amp

The Easee Equalizer Amp is a measurement device and an accessory for the Easee Equalizer. This device provides the data necessary for the Equalizer to balance the energy between your building and the Charging Robot(s). Avoid unnecessary investments in expensive smart meters and install within minutes with our Plug & Play system.





Why choose the Easee Equalizer Amp?

Charge smarter, safer and faster

Through dynamic load and phase management, the Equalizer can take advantage of available electrical capacity. Combined with the Amp, they measure the building's consumption, and use the available energy to charge faster, boosting the charging experience in larger charging sites such as shopping centres, offices, and apartment buildings.

The Amp and Equalizer give you everything necessary to use solar panels, or any other renewable energy source, to charge your car.

Super fast installation with Plug & Play, you are up and running within minutes.



Benefits of the Easee Equalizer Amp



Dynamic load balancing without a smart meter

Charge your EVs faster when the building's energy consumption is lower and avoid overload and power interruptions.



Streamline installation of hundreds of chargers

Avoid expensive infrastructure upgrades or limitations of grid capacity with fuse balancing.



Solar charging without a smart meter

Enable full utilization from your building's solar panels or any renewable energy source.




6x faster charging


When energy consumption is lower, more energy is available to the Charging Robot(s), so you can charge up to 6x faster.

Specifications

Measurement

in mm





Technical

General

Dimensions (mm): H: $95 \times W$: $51 \times D$: 30Operating temperature: -20 °C to +50 °C

Weight: 105 g Supply: 85-264 VAC

Installation system: TT, IT or TN $\,$

Phases: 1- or 3-phase

Current sensors

Type: CT clamps

Operation range: 0 - 100 A Conductor diameter: max. 16 mm

Cable length: 1,5 m

Protection

Degree of protection: IP30 Insulation class: II

Overvoltage category: OVC II

Connectivity

2x RJ12

6x sensor slots

1x 12 pin expansion port

The product contains



Equalizer Amp



Power Cable



Current sensors x3



DIN bracket



Expansion connector

THIS DOCUMENT CONTAINS INFORMATION THAT IS SUBJECT TO CHANGE WITHOUT NOTICE.

The latest version of this publication can be downloaded at http://easee.support

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including, but not limited to, copying, recording, retrieving data, or computer networks without the written permission of Easee AS.

Easee and all other Easee product names and slogans are trademarks or registered trademarks of Easee AS. Easee products can be protected by one or more patents.

All other products and services mentioned may be trademarks or service marks of their respective owners.

Illustrations of the product and user interface are exemplary and may differ from the actual appearance.

November 2022 - Version 1.01 © 2022 by Easee AS. All rights reserved.



Easee AS Grenseveien 19 4313 Sandnes, Norway Org.nr: 920 292 046 Easee is distributed and maintained by a network of qualified partners and resellers. Find more information and your local partner at:

vvvvvv.easee.com